



EcoCOMFORT DATA

0200V1

Model	Flow Rate m3/s	Dimensions			Weight (kg)	Peak Power kW	FLA Amps	LIST PRICE (£ - Ex-works)
		L(mm)	W(mm)	H(mm)				
25	0.25	2325	880	1300	815	2.64	4.23	6865.34
40	0.40	2638	1090	1400	1060	7.04	11.27	8072.00
68	0.68	2950	1300	1500	1330	7.59	12.15	9682.82
90	0.90	3263	1510	1600	1528	14.08	22.54	11027.51
112	1.12	3575	1720	1700	1801	14.52	23.25	12840.17
134	1.34	3888	1930	1800	1982	14.96	23.95	13955.84
156	1.56	4200	2140	1900	2214	19.80	31.70	15121.30
178	1.78	4513	2350	2000	2449	24.09	38.57	16933.96
200	2.00	4825	2560	2100	2650	25.03	40.07	17999.85
222	2.22	5138	2770	2200	2851	25.63	41.04	19065.75
244	2.44	5450	2980	2300	3052	26.07	41.74	20131.64
266	2.66	5763	3190	2400	3254	27.23	43.59	21197.53
288	2.88	6075	3400	2500	3455	27.23	43.59	22263.42
310	3.10	6388	3610	2600	3656	30.86	49.41	23329.31
332	3.32	6700	3820	2700	3681	34.98	56.01	24395.20

Notes

- 1) Units are based R134a refrigerant. Consult our technical team for other refrigerant options.
- 2) Supply 380~415 V / 3 Ph / 50 operation. Consult technical team for other voltages.
- 3) Units require main water supply at least 1 Barg main pressure.

STRICTLY PRIVATE CONFIDENTIAL